

MODEL	ENERGY CLASS (FT LB)	BLOWS PER MINUTE	WEIGHT (LBS)	TOOL DIAMETER (IN)	OIL FLOW (GPM)	MAX OPERATING PRESSURE (PSI)	CARRIER WEIGHT (TONS)
SM1	175	700-1500	158	1.5	2.6-4.2	1600	0.75-1.8
SM2	325	700-1500	326	1.57	4-9	1800	1-3
SM3	400	450-1150	479	2.17	6-14	1900	2-4.5
SM5	550	400-1100	569	2.36	9-16	1900	2.5-6
SM5-SL	550	400-1100	710	2.36	9-16	1900	SKID STEER
SM7	750	500-750	730	2.68	10-18	1900	4-7
SM9	1000	460-750	970	2.93	12-23	1900	5-10
SM10	1500	400-800	1100	3.35	12-24	2200	6-13
SM15	2500	400-750	2156	3.94	21-29	2300	10-16
SM18	3000	400-700	2792	4.72	23-32	2500	13-21
SM20	5000	350-600	4020	5.31	26-40	2600	16-24
SM25	6000	350-500	4410	5.51	32-48	2600	18-26
SM30	7000	300-450	5440	5.91	40-56	2600	25-30
SM35	8000	300-450	5988	6.10	48-64	2600	28-35
SM45	10,000	250-400	7010	6.50	53-69	2600	30-45
SM510	13,500	250-400	9380	7.08	66-79	2320	40-60
SM610	15,000	200-350	12,400	7.68	69-95	2610	48-80